

Comparativa de Especificaciones Técnicas








Mayo 2022



AV.COMPANY - TIENDA ONLINE







Ambient Media & Comunicación S.L. | Plz. Mayor, 5 | 28450 Collado Mediano | Madrid - España
+34 91 325 0849 | info@ambientmedia.es




NDI	UV950AS-ST-NDI Series			UV510AS-ST-NDI Series				
								
Modelo	UV950AS-12-ST-NDI-IR/WR	UV950AS-20-ST-NDI-IR/WR	UV950AS-30-ST-NDI-IR/WR	UV510AS-05-ST-NDI-IR/WR	UV510AS-10-ST-NDI-IR/WR	UV510AS-12-ST-NDI-IR/WR	UV510AS-20-ST-NDI-IR/WR	UV510AS-30-ST-NDI-IR/WR
Color	Black (default) / White (optional)			Silver grey (default) / White and Black (optional)				
Dimensiones	258X172X168 (mm)			150X150X167.5 (mm)				
Peso	1.6 kg			1.4 kg				
Zoom Optico	12X	20X	30X	5X	10X	12X	20X	30x
Zoom Digital	10X			10X				
Angulo de visión	72.5°	54.7°	65.1°	83.7°	60.9°	72.5°	54.7°	65.1°
Resolución	1080P60,59.94,50,30,29.97.25,1080i60,59.94,50,720p60,59.94,50,30,29.97.25			1080P60,59.94,50,30,29.97.25,1080i60,59.94,50,720p60,59.94,50,30,29.97,25				
Formato USB 3.0	1920X1080P60/50/30/25;1280X720P60/50/30/25;960X540P30;640X360P30;			-	-	-	-	-
Formato USB 2.0	✗	✗	✗	✗	✗	✗	✗	✗
USB 3.0 (USB2.0 compatible)	✗	✗	✗	✗	✗	✗	✗	✗
HDMI(DVI)	✓	✓	✓	✓	✓	✓	✓	✓
HD-3G-SDI	✓	✓	✓	✓	✓	✓	✓	✓
CVBS	-	-	-	-	-	-	-	-
IP streaming	✓	✓	✓	✓	✓	✓	✓	✓
RS232-In	✓	✓	✓	✓	✓	✓	✓	✓
RS232-out	✓	✓	✓	✓	✓	✓	✓	✓
RS485	✓	✓	✓	✓	✓	✓	✓	✓
Audio in	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm
Audio out	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet
Opción PoE	✗	✗	✗	De Serie	De Serie	De Serie	De Serie	De Serie





4K	UV401 Series		UV420 Series		UV430A
					
Modelo	UV401A	UV401B	UV420A	UV420B	UV430A
	1/2.5" Sony CMOS sensor	1/1.8" Sony CMOS sensor	1/2.8" Sony CMOS sensor	1/2.5" Sony CMOS sensor	1/2.5" Sony CMOS sensor
Color	Black		Silver grey		Silver grey
Dimensiones	178X115.5X150.9 (mm)		181X115X149 (mm)		220X144X159 (mm)
Peso	1.38 kg		1.15 kg		1.7 kg
Zoom Optico	12X		12X	5X	12X
Zoom Digital	-		10X		-
Angulo de visión	80.4°	82.6°	69.4°	79.18°	80.4°
Resolución (HDMI)	4K@60fps		4K@60fps		4K@60fps
Características	Windows7, Windows8, Windows10, MacOS, Linux, etc		-		-
Formato USB 2.0	X	X	X	X	X
USB 3.0 (USB2.0 compatible)	✓	✓	✓	✓	✓
HDMI(DVI)	✓	✓	✓	✓	✓
HD-3G-SDI	X	X	X	X	X
CVBS	X	X	X	X	X
IP streaming	✓	✓	✓	✓	✓
RS232-In	✓	✓	✓	✓	✓
RS232-out	✓	✓	✓	✓	✓
RS485	✓	✓	✓	✓	✓
Audio in	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm
Audio out	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet
Opción PoE	X	X	Opción	Opción	X

4K	UV430E Series	
		
Modelo	UV430E0	UV430E2
	1/2.5" Sony CMOS sensor	1/1.8" Sony CMOS sensor
Color	Silver grey	Silver grey
Dimensiones	220X144X159 (mm)	220X144X159 (mm)
Peso	1.7 kg	1.7 kg
Zoom Optico	12X	25X
Zoom Digital	–	–
Angulo de visión	80.4°	59.2°
Resolución (HDMI)	4K@60fps	4K@60fps
Características	–	–
Formato USB 2.0	✓	✓
USB 3.0 (USB2.0 compatible)	✗	✗
HDMI(DVI)	✓	✓
HD-3G-SDI	✓	✓
CVBS	✗	✗
IP streaming	✓	✓
RS232-In	✓	✓
RS232-out	✓	✓
RS485	✓	✓
Audio in	jack 3.5mm	jack 3.5mm
Audio out	HDMI, Ethernet, USB2.0	HDMI, Ethernet, USB2.1
Opción PoE	✓	✓

Autoseguimiento	UV100S-T Series				UV220T
					
Modelo	UV100S-T-12	UV100S-T-S20	UV100S-T-12 (4mm)-U	UV100S-T-20 (4mm)-U	UV220T
Color	Black/Dark grey		Black/Dark grey		Dark grey
Dimensiones	258X172X168 (mm)		258X172X168 (mm)		148.8X76X 76 (mm)
Peso	1.6 kg		1.6 kg		0.53 kg
Zoom Optico	12X	20X	12X	20X	-
Zoom Digital	10X		10X		3X
Angulo de visión	72.5°	54.7°	72.5°	54.7°	47°
Resolución	1080P60,59.94,50,30,29.97.25, 1080i60,59.94,50, 720p60,59.94,50,30,29.97.25				1080P@30fps/25fps; 720P@60fps/50fps/30fps/ 25fps;
Formato USB 3.0	1920X1080P60/50/30/25;1280X720P60/50/30/25;960X540P30;640X360P30;				1920X1080P30fps /25 fps; 1280X720P60 fps /50 fps /30 fps /25 fps; 960X540P30fps; 640X360P30 fps; 640X480P30fps; 352X288P30 fps; 960X540P30 fps; 800X600P30 fps;
Formato USB 2.0	X	X	X	X	Compatible
USB 3.0	X	X	✓	✓	✓
HDMI(DVI)	X	X	✓	✓	✓
HD-3G-SDI	✓	✓	X	X	X
IP streaming	✓	✓	✓	✓	✓
RS232-In	✓	✓	✓	✓	✓
RS232-out	X	X	X	X	✓
RS485	X	X	X	X	X
Audio in	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm
Audio out	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet
Opción PoE	X	X	X	X	✓

Videoconferencia	VA200		
			
Modelo	VA200-V	VA200-A	VA200-H
Color	Black	Black	Black
Dimensiones	151.64X131.25X154.5 mm (LxWxH)	200X200X52 mm (LxWxH)	100X62X27mm (LxWxH)
Peso	-	-	-
Cámara	Serie UV540	-	-
Zoom Optico	5X / 10X	-	-
Zoom Digital	5X	-	-
Angulo de visión	83.7°/60.9°	-	-
Resolución (HDMI)	176x144/320x240/320x180/352x288/ 640x480/720x480/720x576/640x360/ 800X600/960X540/1024X576/ 1024X768/1280X720/ 1920X1080P30/25/20/15/10/5	-	Mini DIN6 x2 Power interfacex1 Power switchx1 Mini USB interfacex1
Resolución (CVBS)			
Características	®WeChat, Skype for Business, Zoom, Vidyo, etc.	10 metros, 360° full range	-
USB 3.0 (USB2.0 compatible)	-	-	✓
HDMI(DVI)	-	-	✓
HD-3G-SDI	-	-	✗
CVBS	-	-	✗
Microphone type			-
Pickup distance			-
Audio processing			-
Speaker			-
Audio out			-

Videoconferencia	VA210			VA400
				
Modelo	VA210-V	VA210-A	VA210-H	VA400 4K Autotracking
Color	Black	Black	Black	Black
Dimensiones	156.8X112.6X139.1 mm (LxWxH)	200X200X52 mm (LxWxH)	100X62X27mm (LxWxH)	598X86X77,5 (mm)
Peso	–	–	–	–
Cámara	Serie UV515	–	–	–
Zoom Óptico	3X/10X	–	–	–
Zoom Digital	10X	–	–	5X
Angulo de visión	85° / 68.8°	–	–	120°
Resolución (HDMI)	1920x1080P@30fps/25fps;1280x720P@30fps/25fps;1024x576P@30fps/25fps;960x540P@30fps/25fps;800x448P@30fps/25fps;640x360P@30fps/25fps;320x176P@30fps/25fps	–	Mini DIN6 x2 Power interfacex1 Power switchx1 Mini USB interfacex1	–
Resolución (CVBS)				
Características	®WeChat, Skype for Business, Zoom, Vidyo, etc.	10 metros, 360° full range	–	detección de rostros y localización de fuentes de sonido y seguimiento de voz
USB 3.0 (USB2.0 compatible)	–	–	✓	✓
HDMI(DVI)	–	–	✓	✗
HD-3G-SDI	–	–	✗	✗
CVBS	–	–	✗	✗
Microphone type	–	–	–	6 digital array microphones
Pickup distance	–	–	–	6m
Audio processing	–	–	–	AEC & AGC & ANS & sound source localization
Speaker	–	–	–	2*7W
Audio out	–	–	–	3.5mm lineal

Webcam	MG200C Series			MG101 Series		MG104 Series		MG201 Series	
									
Modelo	MG200C-AM	MG200C-BM	MG200C-HM	MG101A-1	MG101A-2	MG104-1	MG104-2	MG201-1	MG201-2
Color	Dark grey			Black		Black		Black	
Dimensiones	222X93.25X56.5 (mm)			112X65X93 (mm)		102X46X30 (mm)		180X42.5X46.3 (mm)	
Peso	0.53 kg			0.25 kg		0.15 kg		0,30 kg	
Zoom Optico	-	-	-	-	-	-	-	-	-
Zoom Digital	4X	4X	4X	-	-	-	-	10x	10x
Angulo de visión	83°	87°	120°	83°	109°	80°	109°	83°	100°
Resolución	-	-	-	950x540/160x90/320x180/432x240/640x360/800x480/800x600/864x480/960x720/1024x576/1280x720/1600x896/1600x896/1600x896/1600x896/600x896/1600x896/1920x1080/2304x1296/2304x1536/272x144/368x208/384x216/480x272/624x352/912x512/424x240/480x270/484x480/640x480/352x288/320x240/176x144/160x120/P30		1920x1080@30fps/25fps;1600x896@30fps/25fps;1280x720@30fps/25fps;1024x576@30fps/25fps;60x540@30fps/25fps;800x600@30fps/25fps;800x448@30fps/25fps;720x576@30fps/25fps;720x480@30fps/25fps;640x480@30fps/25fps;640x360@30fps/25fps;480x270@30fps/25fps;320x240@30fps/25fps;352x288@30fps/25fps; 320x180@30fps/25fps		-	-
Resolución (USB3.0)	3840x2160@30fps;1920x1080P@30fps/25fps;1280x720P@30fps/25fps;			-	-	-	-	3840*2160@30/2560*1440@30/1920*1080@30/1600*896@30/1280*720@30/1024*576@30/960*540@30/800*600@30/800*448@30/720*576@30/720*480@30/640*480@30/640*360@30/480*270@30/352*288@30/320*240@30/320*180@30	
USB 2.0 (Plug & Play)	x	x	x	✓	✓	✓	✓	x	x
USB 3.0	✓	✓	✓	x	x	x	x	✓	✓
Características	4K UHD ePTZ			power supply, upgrading available		power supply, upgrading available		4K UHD ePTZ	

UV510A



Modelo	UV510AS-05-ST-IR/WR	UV510AS-10-ST-IR/WR	UV510AS-12-ST-IR/WR	UV510AS-20-ST-IR/WR	UV510AS-30-ST-IR/WR	UV510AS-05-U3-IR/WR	UV510AS-10-U3-IR/WR	UV510AS-12-U3-IR/WR	UV510AS-20-U3-IR/WR	UV510AS-30-U3-IR/WR
Color	Silver grey(default) / White and Black(optional)					Silver grey(default) / White and Black(optional)				
Dimensiones	150X150X167.5 (mm)					150X150X167.5 (mm)				
Peso	1.4 kg					1.4 kg				
Zoom Optico	5X	10X	12X	20X	30x	5X	10X	12X	20X	30x
Zoom Digital	10X					10X				
Angulo de visión	83.7°	60.9°	72.5°	54.7°	65.1°	83.7°	60.9°	72.5°	54.7°	65.1°
Resolución	1080P60,59.94,50,30,29.97.25,1080i60,59.94,50,720p60,59.94,50,30,29.97,25					-				
Formato USB 3.0	-					1920X1080P60/50/30/25 ; 1280X720P60/50/30/25 ; 960X540P30 ; 640X360P30 ; 640X480P30 ; 352X288P30 ; 960X540P30 ; 800X600P30 ; 800*600P30(for usb3.0 output only)				
USB2.0 (compatible)	-					960X540P30;640X360P30;1280X720P10/15;720X576P50;720X480P60;(for usb3.0 output only)				
Formato USB 2.0	X	X	X	X	X	X	X	X	X	X
USB 3.0	X	X	X	X	X	✓	✓	✓	✓	✓
HDMI	✓	✓	✓	✓	✓	X	X	X	X	X
HD-3G-SDI	✓	✓	✓	✓	✓	X	X	X	X	X
IP streaming	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
RS232-In	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
RS232-out	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
RS485	✓	✓	✓	✓	✓	X	X	X	X	X
Audio in	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm
Audio out	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet
HD-BaseT	-	-	-	-	-	-	-	-	-	-
Opción PoE	Opción	Opción	Opción	Opción	Opción	X	X	X	X	X

UV510A



Modelo	UV510AS-05-U2-IR/WR	UV510AS-10-U2-IR/WR	UV510AS-12-U2-IR/WR	UV510AS-20-U2-IR/WR	UV510AS-30-U2-IR/WR	UV510AS-05-HDBASET-IR/WR	UV510AS-10-HDBASET-IR/WR	UV510AS-12-HDBASET-IR/WR	UV510AS-20-HDBASET-IR/WR	UV510AS-30-HDBASET-IR/WR
Color	Silver grey(default) / White and Black(optional)					Silver grey(default) / White and Black(optional)				
Dimensiones	150X150X167.5 (mm)					150X150X167.5 (mm)				
Peso	1.4 kg					1.4 kg				
Zoom Optico	5X	10X	12X	20X	30x	5X	10X	12X	20X	30x
Zoom Digital	10X					10X				
Angulo de visión	83.7°	60.9°	72.5°	54.7°	65.1°	83.7°	60.9°	72.5°	54.7°	65.1°
Resolución	176x144/320x240/320x180/352x288/640x480/720x480/720x576/640x360/800X600/960X540/1024X576/1024X768/1280X720/1920X1080 /					1080P60,59.94,50,30,29.97.25,1080i60,59.94,50,720p60,59.94,50,30,29.97,25				
Formato USB 3.0	-					-				
USB2.0 (compatible)	176x144/320x240/320x180/352x288/640x480/720x480/720x576/640x360/800X600/960X540/1024X576/1024X768/1280X720/1920X1080P30/25/20/15/10/5					-				
Formato USB 2.0	✓	✓	✓	✓	✓	✗	✗	✗	✗	✗
USB 3.0	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗
HDMI	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗
HD-3G-SDI	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗
IP streaming	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
RS232-In	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
RS232-out	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
RS485	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗
Audio in	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm
Audio out	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet
HD-BaseT	-	-	-	-	-	✓	✓	✓	✓	✓
Opción PoE	✗	✗	✗	✗	✗	De Serie	De Serie	De Serie	De Serie	De Serie

UV515A



Modelo	UV515-3X	UV515-10X
Color	Black	
Dimensiones	156,8X112,6X139,5 (mm)	
Peso	1 kg	
Zoom Optico	3X	10X
Zoom Digital	10X	
Angulo de visión	85°	68.8°
Resolución	1920 × 1080P a 30 fps / 25 fps; 1280 × 720P @ 30fps / 25fps; 1024 × 576P @ 30fps / 25fps; 960 × 540P @ 30fps / 25fps; 800 × 448P @ 30fps / 25fps; 640 × 360P @ 30fps / 25fps; 320 × 176P a 30 fps / 25 fps	
Formato USB 3.0	-	
USB2.0 (compatible)	-	
Formato USB 2.0	✓	✓
HDMI	✗	✗
HD-3G-SDI	✗	✗
IP streaming	✓	✓
RS232-In	✓	✓
RS232-out	✓	✓
RS485	✓	✓
Audio in	jack 3.5mm	jack 3.5mm
Audio out	Ethernet	Ethernet
Opción PoE	✗	✗

UV950A									
	Modelo	UV950AS-12-ST-IR/WR	UV950AS-20-ST-IR/WR	UV950AS-30-ST-IR/WR	UV950AS-12-U3-IR/WR	UV950AS-20-U3-IR/WR	UV950AS-30-U3-IR/WR	UV950AS-12-U2U3-IR/WR	UV950AS-20-U2U3-IR/WR
Color	Black (default) / White (optional)			Black (default) / White (optional)			Black (default) / White (optional)		
Dimensiones	258X172X168 (mm)			258X172X168 (mm)			258X172X168 (mm)		
Peso	1.6 kg			1.6 kg			1.6 kg		
Zoom Optico	12X	20X	30X	12X	20X	30X	12X	20X	30X
Zoom Digital	10X			10X			10X		
Angulo de visión	72.5°	54.7°	65.1°	72.5°	54.7°	65.1°	72.5°	54.7°	65.1°
Resolución	1080P60,59.94,50,30,29.97.25,1080i60,59.94,50,720p60,59.94,50,30,29.97.25			1080P60,59.94,50,30,29.97.25,1080i60,59.94,50,720p60,59.94,50,30,29.97.25			1080P60,59.94,50,30,29.97.25,1080i60,59.94,50,720p60,59.94,50,30,29.97.25		
Formato USB 3.0	1920X1080P60/50/30/25;1280X720P60/50/30/25;960X540P30;640X360P30;			1920X1080P60/50/30/25;1280X720P60/50/30/25;960X540P30;640X360P30;			1920X1080P60/50/30/25;1280X720P60/50/30/25;960X540P30;640X360P30;		
USB2.0 compatible	960X540P30;640X360P30;1280X720P10/15;720X576P50;20X480P60;640X480P30;352X288P30;800X600P30			960X540P30;640X360P30;1280X720P10/15;720X576P50;720X480P60;640X480P30;352X288P30;800X600P30			960X540P30;640X360P30;1280X720P10/15;720X576P50;720X480P60;640X480P30;352X288P30;800X600P30		
Formato USB 2.0	X	X	X	X	X	X	✓	✓	✓
USB 3.0	X	X	X	✓	✓	✓	✓	✓	✓
HDMI(DVI)	✓	✓	✓	✓	✓	✓	✓	✓	✓
HD-3G-SDI	✓	✓	✓	X	X	X	X	X	X
IP streaming	✓	✓	✓	✓	✓	✓	✓	✓	✓
RS232-In	✓	✓	✓	✓	✓	✓	✓	✓	✓
RS232-out	✓	✓	✓	X	X	X	X	X	X
RS485	✓	✓	✓	X	X	X	X	X	X
Audio in	jack 3.5mm	jack 3.5mm	jack 3.5mm	X	X	X	jack 3.5mm	jack 3.5mm	jack 3.5mm
Audio out	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet
Opción PoE	Opción	Opción	Opción	X	X	X	X	X	X

UV540										
	Modelo	UV540-05-SDI-W/G	UV540-10-SDI-W/G	UV540-05-HDMI-W/G	UV540-10-HDMI-W/G	UV540-05-U3-W/G	UV540-10-U3-W/G	UV540-05-U2-W/G	UV540-10-U2-W/G	UV540-5-U3-HDMI-W/G
Color	White/Grey		White/Grey		White/Grey		White/Grey		White/Grey	
Dimensiones	151.2X152.5X126.7 (mm)		151.2X152.5X126.7 (mm)		151.2X152.5X126.7 (mm)		151.2X152.5X126.7 (mm)		151.2X152.5X126.7 (mm)	
Peso	1.4 kg		1.4 kg		1.4 kg		1.4 kg		1.4 kg	
Zoom Optico	5X/10X		5X/10X		5X/10X		5X/10X		5X/10X	
Zoom Digital	5X		5X		5X		5X		5X	
Angulo de visión	5X:20°/83.7° 10X:6.43°/60.9°		5X:20°/83.7° 10X:6.43°/60.9°		5X:20°/83.7° 10X:6.43°/60.9°		5X:20°/83.7° 10X:6.43°/60.9°		5X:20°/83.7° 10X:6.43°/60.9°	
Resolución	1080P60/50/30/25/59.94/29.97;1080I60/50/59.94;720P60/50/30/25/59.94/29.97 (for both four SDI/HDMI models)									
Formato USB 3.0	1920X1080P60/50/30/25;1280X720P60/50/30/25;960X540P30;640X360P30;640X480P30;352X288P30;960X540P30;800X600P30;800*600P30(for usb3.0 output only)									
USB2.0 compatible	960X540P30;640X360P30;1280X720P10/15;720X576P50; 720X480P60;640X480P30;352X288P30;(for usb3.0 output only)									
Formato USB 2.0	176x144/320x240/320x180/352x288/640x480/720x480/720x576/ 640x360/800X600/960X540/1024X576/1024X768/1280X720/1920X1080 / P30/25/20/15/10/5(usb2.0 output)									
USB 3.0	X	X	X	X	✓	✓	X	X	✓	✓
USB2.0	X	X	X	X	X	X	✓	✓	X	X
HDMI	X	X	✓	✓	X	X	X	X	✓	✓
HD-3G-SDI	✓	✓	X	X	X	X	X	X	X	X
IP streaming	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
RS232-In	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
RS232-out	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Audio in	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	X	X	X	X	X	X
Audio out	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet
Opción PoE	De Serie	De Serie	De Serie	De Serie	X	X	X	X	X	X

UV570	UV570-SU Series			UV570-ST Series			UV570-U3 Series		
									
Modelo	UV570-12-SU-IR	UV570-20-SU-IR	UV570-30-SU-IR	UV570-12-ST-IR	UV570-20-ST-IR	UV570-30-ST-IR	UV570-12-U3-IR	UV570-20-U3-IR	UV570-30-U3-IR
Color	Black/Dark grey			Black/Dark grey			Black/Dark grey		
Dimensiones	178X115.5X150.9 (mm)			178X115.5X150.9 (mm)			178X115.5X150.9 (mm)		
Peso	1.38 kg			1.38 kg			1.38 kg		
Zoom Optico	12X	20X	30X	12X	20X	30X	12X	20X	30X
Zoom Digital	10X			10X			10X		
Angulo de visión	72.5°	54.7°	65.1°	72.5°	54.7°	65.1°	72.5°	54.7°	65.1°
Resolución (HDMI)	1080P60,59.94,50,30,29.97.25,1080i60,59.94,50,720p60,59.94,50,30,29.97.25			1080P60,59.94,50,30,29.97.25,1080i60,59.94,50,720p60,59.94,50,30,29.97.25			1080P60,59.94,50,30,29.97.25,1080i60,59.94,50,720p60,59.94,50,30,29.97.25		
Resolución (CVBS)	570i 480i			570i 480i			570i 480i		
Resolución (USB3.0)	1920x1080@60fps Máx.			1920x1080@60fps Máx.			1920x1080@60fps Máx.		
Resolución (USB2.0)	1080P@30fps Máx.			1080P@30fps Máx.			1080P@30fps Máx.		
Formato USB 2.0	✓	✓	✓	✓	✓	✓	✓	✓	✓
Formato USB 3.0	✓	✓	✓	✗	✗	✗	✓	✓	✓
HDMI(DVI)	✓	✓	✓	✓	✓	✓	✓	✓	✓
HD-3G-SDI	✓	✓	✓	✓	✓	✓	✗	✗	✗
CVBS	✗	✗	✗	✗	✗	✗	✗	✗	✗
IP streaming	✓	✓	✓	✓	✓	✓	✓	✓	✓
RS232-In	✓	✓	✓	✓	✓	✓	✓	✓	✓
RS232-out	✓	✓	✓	✓	✓	✓	✓	✓	✓
RS485	✓	✓	✓	✓	✓	✓	✓	✓	✓
Audio in	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm
Audio Embebido	Ethernet, USB, HDMI, SDI	Ethernet, USB, HDMI, SDI	Ethernet, USB, HDMI, SDI	Ethernet, USB, HDMI, SDI	Ethernet, USB, HDMI, SDI	Ethernet, USB, HDMI, SDI	Ethernet, USB, HDMI, SDI	Ethernet, USB, HDMI, SDI	Ethernet, USB, HDMI, SDI
Opción PoE	De Serie	De Serie	De Serie	✗	✗	✗	De Serie	De Serie	De Serie

Fijas								
Modelo	UV1301S	UV1301S-POE	UV1302M-SDI	UV1302M-U2	UV1202	UV1201S-T20	UV1201S-S20	UV1201A-S20
Color	Silver white		Silver white		Silver grey	Grey		
Dimensiones	126.8X55X58.6 (mm)		155X142X155 (mm)		154.5X154.5X149.3 (mm)	155.7X70X70 (mm)		
Peso	0.5 kg		1.6 kg		-	0.7 kg		
Zoom Optico	-	-	-	-	5X/10X/12X/20X	20X		
Zoom Digital	5X		3X		10X	10X		
Angulo de visión	-	-	-	-	-	55.4°	54.7°	54.7°
Resolución	1080P60,59.94,50,30,29.97.25,1080i60,59.94,50,720p60,59.94,50,30,29.97.25							
Formato USB 2.0	X	X	X	✓	X	X	X	X
HDMI(DVI)	X	X	X	X	X	✓	✓	✓
HD-3G-SDI	✓	✓	✓	X	✓	✓	✓	✓
IP streaming	✓	✓	✓	✓	✓	✓	✓	✓
RS232-In	X	X	✓	✓	✓	X	X	X
RS232-out	X	X	✓	✓	✓	X	X	X
RS485	✓	✓	✓	✓	✓	✓	✓	✓
Audio in	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm	jack 3.5mm
Audio out	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet
Opción PoE	X	De Serie	X	X	X	X	X	X

Controladores		
Modelo	KBD1010	KBD2000
Color	Black/Dark grey	Black
Dimensiones	258X172X168 (mm)	320X179.3X109.9 (mm)
Peso	-	-
Aplicaciones	All cameras	All cameras

Accesorios							
Modelo	Wall mount	Ceiling bracket	UV540 wall	UV540 ceiling	Remote	Remote	Power supply
Color	White and Black	Black only	Black/White/Grey	Black only	Black	White	Black
Dimensiones	100X60X35 (mm)	84X56X8 (mm)	23X13.5X8 (mm)	-	-	-	-
Peso	0.72 kg	0.54 kg	-	-	-	-	-
Aplicaciones	UV950A, UV510A, UV100T, UV430A, UV401A	UV950A, UV510A, UV100T, UV430A, UV401A	UV540 only	UV540 only	-	-	-